


XT Series DD Servo Motors

XT系列直驱力矩电机





Company Profile 企业简介

宁波菲仕技术股份有限公司（简称：菲仕技术）成立于 2001 年，由民营控股、先进制造产业投资基金和宁波通商集团等战略投资人参股，公司致力于以“高效节能、精准控制”电驱动技术为核心的创新及产业化，为运动控制和能量转换领域提供系统产品和综合解决方案，经过多年品牌沉淀，菲仕已成为一家集研发、生产、销售为一体，拥有国内外多家控股子公司的集团化创新型高科技企业。

Ningbo Physis Technology Co., Ltd. (hereinafter referred to as Physis) was founded in 2001. Physis always devotes to innovation and industrialization of electrical drive technology, provides servo products and solutions for the field of motion control & energy conversion. After years of brand development and accumulation, Physis becomes a collectivized & innovative high-tech enterprise, which collects together R&D, manufacturing and sales, and has a numbers of domestic and overseas subsidiaries.

Global presence 全球布局

立足全国 放眼全球

总部“永动谷”落户中国宁波北仑，在国内产业链完善的宁波、株洲、天津、赣州建立大型生产基地。建立国内外分子公司 17 家，合作伙伴百余家，形成覆盖全国、面向全球市场的营销服务网络，逐步落地国际化战略。

Physis has established large-scale production bases in Ningbo, Zhuzhou, Tianjin, and Guangzhou, which have a complete domestic industrial chain.

It has established 17 domestic and foreign subsidiaries and more than 100 partners, formed a marketing service network covering the whole country and facing the global market, and gradually implemented the internationalization strategy.

CONTENTS 目录

产品特点 Product Features	01
应用领域 Application	02
XT 系列伺服电机代码 Servo Motor Code	02
XT210	03
XT295	07
XT360	11
XT450	15
XT530	19
XT760	21
XT990	23
XT1220	25
联系我们 Contact Information	27

Product Features

产品特点

高功率密度

XT 系列通过新工艺线圈排布技术，大幅提升了槽满率，使得电机在扭矩密度达到行业领先水平。

强工艺技术

采用先进的真空环氧浇注工艺，并辅以独特的冷却结构设计。这一组合不仅显著增强了电机的散热性能，提高了绝缘等级，还大大增强了电机的结构稳定性，确保电机在长时间、高负荷运行下的可靠性。

紧凑设计

电机结构紧凑，无框设计便于集成在 A 轴、B 轴、C 轴内部，适应各种空间紧凑、高扭矩的严苛应用场景，方便安装与维护。

系列化全面覆盖


该系列电机定子外径范围覆盖 210mm ~ 1220mm，扭矩范围从 60 牛米扩展至 5 万牛米。广泛适用于机床行业的五轴机床、直驱摇篮转台和直驱摆头等高性能需求的应用场合，为现代工业制造提供了强有力的动力支持。

High Power Density: The XT series, through innovative coil arrangement technology, has significantly increased the slot fill rate, allowing the motor to achieve industry-leading levels of torque density.


Robust Craftsmanship: Utilizing advanced vacuum epoxy pouring techniques, complemented by a unique cooling structure design. This combination not only significantly enhances the motor's heat dissipation capabilities and insulation level but also greatly strengthens the structural stability of the motor, ensuring reliability during long periods of high-load operation.

Compact Design: The motor features a compact structure with a frameless design that facilitates integration within the A-axis、B-axis、C-axis, adapts to various space-constrained, high-torque demanding application scenarios, and simplifies installation and maintenance.

standardization & serialization: This series of motors covers a stator outer diameter range from 210mm to 1220mm, with torque ranging from 60 Nm to 50,000 Nm. It is widely applicable to high-performance requirements in the machine tool industry, such as five-axis machine tools, direct-drive cradle rotary tables, and direct-drive swing heads, providing robust power support for modern industrial manufacturing.



Application 应用领域



Servo Motor Code XT 系列伺服电机代码

XT - 360 - 070 - 000C

集中绕组
电机代码

Concentrated
Winding
Motor Coding

电机基座识别：
电机定子外径 (mm)
210、295、360、450

Machine base
identification:
Motor stator outer
diameter (mm)
210、295、360、450

电机高度识别：
定子冲片叠厚度 (mm)
30、50、70、100、
150、200

Motor height
identification: Stator
lamination stack
thickness (mm)
30、50、70、100、
150、200

标准款电机代码

Standard motor code

订购代码示例：

XT360-070-000C

定子外径 360mm，叠厚 70mm 的标准款集中绕组力矩电机

Order Code Example:













XT360-070-000C













The outer diameter of the stator is 360mm, and the stacking thickness is 70mm

XT210

性能参数 Performance parameters

电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT210-030-050C	50	200	3.5	60	0.3	6.5	110
XT210-030-100C	100	200	3.5	60	0.6	6.5	110
XT210-030-150C	150	300	4.9	60	0.94	9.5	110
XT210-030-200C	200	400	4.9	60	1.257	9.5	110
XT210-050-050C	50	200	5.1	100	0.5	10.3	200
XT210-050-100C	100	200	5.1	100	1	10.3	200
XT210-050-150C	150	300	6.8	100	1.6	14	200
XT210-050-200C	200	400	6.8	100	2.1	14	200
XT210-070-050C	50	200	7	145	0.8	14.2	290
XT210-070-100C	100	200	7	145	1.5	14.2	290
XT210-070-150C	150	300	9	145	2.3	18.5	290
XT210-070-200C	200	400	11.6	145	3	24	290
XT210-100-050C	50	200	9.2	210	1.1	18.6	420
XT210-100-100C	100	200	10.2	210	2.2	18.6	420
XT210-100-150C	150	300	11.6	210	3.3	24	420
XT210-100-200C	200	400	14	210	4.4	28	420
XT210-150-050C	50	200	14	320	1.7	29	640
XT210-150-100C	100	200	14	320	3.4	29	640
XT210-150-150C	150	300	18.2	320	5	36.5	640
XT210-150-200C	200	400	23.2	320	6.7	48	640
XT210-200-050C	50	200	18.2	420	2.2	37.5	850
XT210-200-100C	100	200	20.5	420	4.4	43	850
XT210-200-150C	150	300	23.2	420	6.6	47	850
XT210-200-200C	200	400	28	420	8.8	57	850






XT210

尺寸参数 Dimensional parameters













电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT210-030-000C	230	230	175	173.8	140	70	30	19.5	12*M5	12*M5	12*M5	12*M5
XT210-050-000C	230	230	175	173.8	140	90	50	19.5	12*M5	12*M5	12*M5	12*M5
XT210-070-000C	230	230	175	173.8	140	110	70	19.5	12*M5	12*M5	12*M5	12*M5
XT210-100-000C	230	230	175	173.8	140	140	100	19.5	23*M5	24*M5	23*M5	24*M5
XT210-150-000C	230	230	175	173.8	140	190	150	19.5	23*M5	24*M5	23*M5	24*M5
XT210-200-000C	230	230	175	173.8	140	240	200	19.5	23*M5	24*M5	23*M5	24*M5



XT295


性能参数 Performance parameters

电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT295-030-050C	50	200	6.5	140	0.7	13	280
XT295-030-100C	100	200	6.5	140	1.5	13	280
XT295-030-150C	150	300	9.1	140	2.2	19	280
XT295-030-200C	200	400	9.1	140	2.9	19.3	280
XT295-050-050C	50	200	9.2	250	1.3	21	500
XT295-050-100C	100	200	9.2	250	2.6	21	500
XT295-050-150C	150	300	14	250	3.9	32	500
XT295-050-200C	200	400	14	250	5.2	32	500
XT295-070-050C	50	200	11.7	350	1.8	27	700
XT295-070-100C	100	200	11.7	350	3.7	27	700
XT295-070-150C	150	300	18.2	350	5.5	39	700
XT295-070-200C	200	400	21	350	7.3	48	700
XT295-100-050C	50	200	14	500	2.6	31	1000
XT295-100-100C	100	200	18.3	500	5.2	42	1000
XT295-100-150C	150	300	27.5	500	7.9	64	1000
XT295-100-200C	200	400	27.5	500	10.5	64	1000
XT295-150-050C	50	200	23	750	3.9	52.3	1500
XT295-150-100C	100	200	23	750	7.9	52.3	1500
XT295-150-150C	150	300	34.6	750	11.8	78	1500
XT295-150-200C	200	400	42	750	15.7	99	1500




XT295-100-050C

SPEED - FLUX WEAKENING




XT295-150-050C

SPEED - FLUX WEAKENING




XT295-100-100C

SPEED - FLUX WEAKENING




XT295-150-100C

SPEED - FLUX WEAKENING




XT295-100-150C

SPEED - FLUX WEAKENING




XT295-150-150C

SPEED - FLUX WEAKENING




XT295-100-200C

SPEED - FLUX WEAKENING



XT295-150-200C


SPEED - FLUX WEAKENING



XT295

尺寸参数 Dimensional parameters













电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT295-030-000C	310	310	255	253.8	220	70	30	19.5	12*M5	12*M5	12*M5	12*M5
XT295-050-000C	310	310	255	253.8	220	90	50	19.5	12*M5	12*M5	12*M5	12*M5
XT295-070-000C	310	310	255	253.8	220	110	70	19.5	12*M5	12*M5	12*M5	12*M5
XT295-100-000C	310	310	255	253.8	220	140	100	19.5	23*M5	24*M5	24*M5	24*M5
XT295-150-000C	310	310	255	253.8	220	190	150	19.5	23*M5	24*M5	24*M5	24*M5















XT360

性能参数 Performance parameters

电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT360-030-050C	50	200	7.4	230	1.2	15.5	450
XT360-030-100C	100	200	9.5	230	2.4	20	450
XT360-030-150C	150	300	11.4	230	3.6	24.5	450
XT360-030-200C	200	400	14.2	230	4.8	30	450
XT360-050-050C	50	200	10	405	2.1	21	740
XT360-050-100C	100	200	12	405	4.2	23.5	740
XT360-050-150C	150	300	19.8	405	6.4	39	740
XT360-050-200C	200	400	24.2	405	8.5	48.5	740
XT360-070-050C	50	200	16	575	3	32	1030
XT360-070-100C	100	200	20.5	575	6	39	1030
XT360-070-150C	150	300	23.8	575	9	48	1030
XT360-070-200C	200	400	30.8	575	12	60	1030
XT360-100-050C	50	200	20.5	845	4.4	40	1470
XT360-100-100C	100	200	25.3	845	8.8	47	1470
XT360-100-150C	150	300	38	845	13.3	72	1470
XT360-100-200C	200	400	48.5	845	17.7	96	1470
XT360-150-050C	50	200	25.5	1270	6.6	51	2210
XT360-150-100C	100	200	38.5	1270	13.3	71	2210
XT360-150-150C	150	300	49	1270	19.9	100	2210
XT360-150-200C	200	400	73	1270	26.6	140	2210
XT360-200-050C	50	400	32	1700	8.9	58	2950
XT360-200-100C	100	200	46.5	1700	17.8	88	2950
XT360-200-150C	150	300	77	1700	26.7	140	2950
XT360-200-200C	200	400	93	1700	35.6	175	2950






XT360

尺寸参数 Dimensional parameters













电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT360-030-000C	385	385	313	311	265	80	30	29.5	12*M6	12*M6	12*M6	12*M6
XT360-050-000C	385	385	313	311	265	100	50	29.5	12*M6	12*M6	12*M6	12*M6
XT360-070-000C	385	385	313	311	265	120	70	29.5	12*M6	12*M6	12*M6	12*M6
XT360-100-000C	385	385	313	311	265	150	100	29.5	23*M6	24*M6	23*M6	24*M6
XT360-150-000C	385	385	313	311	265	200	150	29.5	23*M6	24*M6	23*M6	24*M6
XT360-200-000C	385	385	313	311	265	250	200	29.5	23*M6	24*M6	23*M6	24*M6















XT450

性能参数 Performance parameters

电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT450-030-050C	50	100	8.4	380	2	18.8	710
XT450-030-100C	100	200	15.6	380	4	35	710
XT450-030-150C	150	300	23.4	380	6	52.5	710
XT450-030-200C	200	400	31.2	380	8	70	710
XT450-050-050C	50	100	14.4	680	3.6	32.2	1210
XT450-050-100C	100	200	25	682	7.1	56	1210
XT450-050-150C	150	300	38.2	680	10.7	85.6	1210
XT450-050-200C	200	400	50	680	14.2	112	1210
XT450-070-050C	50	100	19.65	960	5	44.2	1690
XT450-070-100C	100	200	32	960	10.1	72	1690
XT450-070-150C	150	300	48.2	960	15.1	108.5	1690
XT450-070-200C	200	400	64	960	20.1	144	1690
XT450-100-050C	50	100	25	1370	7.2	55	2420
XT450-100-100C	100	200	50	1370	14.3	110	2420
XT450-100-150C	150	300	61.6	1370	21.5	144	2420
XT450-100-200C	200	400	83	1370	28.7	182.5	2420
XT450-150-050C	50	100	38.5	2050	10.7	84	3560
XT450-150-100C	100	200	63	2050	21.5	140	3560
XT450-150-150C	150	300	96	2050	32.2	201	3450
XT450-150-200C	200	400	136	2050	42.9	278	3450
XT450-200-050C	50	100	50.5	2800	14.7	103	4630
XT450-200-100C	100	200	94	2800	29.3	205	4830
XT450-200-150C	150	300	133	2800	44	278	4650
XT450-200-200C	200	400	180	2800	58.6	378	4650






XT450

尺寸参数 Dimensional parameters






电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT450-030-000C	485	485	384	382.2	345	90	30	37.5	12*M8	12*M8	12*M8	12*M8
XT450-050-000C	485	485	384	382.2	345	110	50	37.5	12*M8	12*M8	12*M8	12*M8
XT450-070-000C	485	485	384	382.2	345	130	70	37.5	12*M8	12*M8	12*M8	12*M8
XT450-100-000C	485	485	384	382.2	345	160	100	37.5	23*M8	24*M8	23*M8	24*M8
XT450-150-000C	485	485	384	382.2	345	210	150	37.5	23*M8	24*M8	23*M8	24*M8
XT450-200-000C	485	485	384	382.2	345	260	200	37.5	23*M8	24*M8	23*M8	24*M8



XT530

性能参数 Performance parameters


电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大扭矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT530-050-000C	110	300	26.1	1041	12.0	64.0	1700
XT530-075-000C	75	300	55.0	1538	12.1	124.0	2500
XT530-100-000C	120	350	56.4	2089	26.2	137.0	3500
XT530-150-000C	150	400	57.3	3342	52.5	154.0	5500
XT530-200-000C	110	350	114.8	4459	51.4	278.0	7000



XT530

尺寸参数 Dimensional parameters






电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT530-050-000C	565	565	460	457.6	420	110	50	29.5	12*M8	12*M8	12*M8	12*M8
XT530-075-000C	565	565	460	457.6	420	130	75	29.5	12*M8	12*M8	12*M8	12*M8
XT530-100-000C	565	565	460	457.6	420	160	100	29.5	23*M8	23*M8	24*M8	24*M8
XT530-150-000C	565	565	460	457.6	420	210	150	29.5	23*M8	23*M8	24*M8	24*M8
XT530-200-000C	565	565	460	457.6	420	260.0	200	29.5	23*M8	23*M8	24*M8	24*M8



XT760

性能参数 Performance parameters


电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT760-050-000C	105	300	52.1	2156	23.7	164.0	3800
XT760-075 -000C	105	300	82.2	3357	36.9	226.0	5500
XT760-100-000C	75	300	84.3	4553	35.8	263.0	7800
XT760-150-000C	115	400	164.1	6507	78.4	415.0	11600
XT760-200-000C	85	300	164.8	8707	77.5	417.0	15500



XT760

尺寸参数 Dimensional parameters





电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT760-050-000C	795	795	690	687.6	650	130	50	39.5	16*M8	16*M8	16*M8	16*M8
XT760-075-000C	795	795	690	687.6	650	150	75	39.5	16*M8	16*M8	16*M8	16*M8
XT760-100-000C	795	795	690	687.6	650	180	100	39.5	31*M8	31*M8	32*M8	32*M8
XT760-150-000C	795	795	690	687.6	650	230	150	39.5	31*M8	31*M8	32*M8	32*M8
XT760-200-000C	795	795	690	687.6	650	280	200	39.5	31*M8	31*M8	32*M8	32*M8



XT990

性能参数 Performance parameters


电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT990-075-000C	80	200	105.3	5823	48.3	277	9800
XT990-100-000C	125	300	215.3	7894	101.5	629	13800
XT990-150-000C	80	250	218.7	11794	98.1	637	20500
XT990-200-000C	60	200	218.7	15720	95.4	646	27500



XT990

尺寸参数 Dimensional parameters






电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT990-075-000C	1030	1030	915	912.6	870	150	75	39.5	24*M10	24*M10	23*M10	23*M10
XT990-100-000C	1030	1030	915	912.6	870	180	100	39.5	24*M10	24*M10	23*M10	23*M10
XT990-150-000C	1030	1030	915	912.6	870	230	150	39.5	24*M10	24*M10	23*M10	23*M10
XT990-200-000C	1030	1030	915	912.6	870	280	200	39.5	24*M10	24*M10	23*M10	23*M10



XT1220

性能参数 Performance parameters


电机型号 Motor Code	额定转速 wn	峰值转速 wmax	额定电流 In	额定扭矩 Tn	额定功率 Pn	最大电流 Imax	最大转矩 Tmax
	[rpm]	[rpm]	[A]	[Nm]	[kW]	[A]	[Nm]
XT1220-050-000C	210	500	256.8	6130	128.8	733	10500
XT1220-075-000C	135	400	270.5	9542	131.1	629	15000
XT1220-100-000C	45	200	138.7	12937	60.9	322	20000
XT1220-150-000C	65	250	281.9	19627	128.1	793	32000
XT1220-200-000C	45	200	282	26171	124.6	790	42600



XT1220

尺寸参数 Dimensional parameters

电机型号 Motor Code	DS1	DS2	DS3	DR1	DR2	LS1	LR1	L	N1*AS1	N2*AS3	N3*AR1	N4*AR3
XT1220-050-000C	1290	1288	1150	1147.6	1070	110	50	39.5	46*M10	48*M10	48*M10	48*M10
XT1220-075-000C	1290	1288	1150	1147.6	1070	130	75	39.5	46*M10	48*M10	48*M10	48*M10
XT1220-100-000C	1290	1288	1150	1147.6	1070	160	100	39.5	46*M10	48*M10	48*M10	48*M10
XT1220-150-000C	1290	1288	1150	1147.6	1070	210	150	39.5	46*M10	48*M10	48*M10	48*M10
XT1220-200-000C	1290	1288	1150	1147.6	1070	260	200	39.5	46*M10	48*M10	48*M10	48*M10



菲仕总部 PHYSIS HEADQUARTER

宁波菲仕技术股份有限公司

Ningbo Physis Technology Co., Ltd.

浙江省宁波市北仑区小港安居路 308 号

No.308, Xiaogang Anju Road, Beilun District, Ningbo, China

总台热线 /Tel: +0086-(0)574-26922600

国内业务 Domestic Sales

销售热线 /Tel: +0086-(0)574-23459197

邮箱 /E-mail: Sales@physis.com.cn

海外业务 Overseas Sales

销售热线 /Tel: +0086-(0)574-23459168

邮箱 /E-mail: OverseaSales@physis.com.cn

售后服务 After Sales

服务热线 /Tel: +0086-(0)574-23459183

邮箱 /E-mail: Aftersales@physis.com.cn



扫一扫了解更多

版本编号：PHMC2505-V02

由于产品的不断更新和改进，本产品型录中的部分产品数据信息会产生变化，为了能提供更好的服务，建议您在查阅本产品型录的同时，请联系我们，以便您及时获得最新的资讯。

All technical data, drawings and product information contained here may be subject to change, in order to provide you with a continuously improved products, please contact with us for up to date information.